

Declaration of Performance

SF15 Sil-Flex Thin Coat Render




DECLARATION OF PERFORMANCE Number: CPR – 275/17

1. Unique identification code of the product-type: **ecorend SF15 Sil-Flex Thin Coat Render**
2. Type, batch or serial number or other identifying mark to identify the construction product as set out in Article 11 (4): **Batch Number: See product packaging**
3. Intended use as foreseen by the manufacturer of the construction product in accordance with the harmonised technical specification: **Internal and external rendering on walls**
4. Name, registered trade name or registered trademark and contact address of the manufacturer as set in article 11 (5): **Wetherby Laroc Group, Dalton Industrial Estate, Dalton, Thirsk, North Yorkshire YO7 3HE**
5. Name and contact address of the authorised representative who has received a mandate for the tasks set out on Article 12 (2): **Not Relevant**
6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with annex V: **System 2+**
7. In the case of declaration of performance concerning a construction product covered by a harmonised standard: **BS EN 15824:2017 - Water diluted external render based on organic binder**
8. In the case of declaration of performance concerning a construction product for which a European Technical assessment has been issued: **Not Relevant**
9. Declared performance

Reaction to fire	Class B (In accordance with Clause 8 of BS EN 13501-1:2018, BS EN 17525:2010 and EN/TS 15117:2005)
Water vapour permeability	V2 (Medium)
Water absorption	W3 (low)
Adhesion	> 0.3MPa
Thermal conductivity	($\lambda_{10, dry}$) 0.66 W/mK (BS EN 1745 Table A.12, mean value; P = 90%)

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance of point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

UK CA MARKING according to UK CA CPR and BS EN 15824:2017

	Wetherby Laroc Group Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE 14
ecorend SF15 Sil-Flex Thin Coat Render Water diluted external render based on organic binder BS EN 15824:2017	
Reaction to fire	Class B (In accordance with Clause 8 of BS EN 13501-1:2018, BS EN 17525:2010 and EN/TS 15117:2005)
Water vapour permeability	V2 (Medium)
Water absorption	W3 (Low)
Adhesion	> 0.3MPa
Thermal conductivity	($\lambda_{10, dry}$) 0.66 W/mK (BS EN 1745 Table A.12 mean value; P = 90%)

Signed for and on behalf of the manufacturer by:

Gavin Bagshaw – Technical Information & Customer Support Lead

Place and date of issue:

5th September 2022 - Dalton/Thirsk

(signature)