



Excellent Adhesion



Water Repellent





Highly Polymer Modified

An Effective Key Coat Base Layer For Multiple Substrates

ecorend K11 Key Coat Base is a cement-based fibre reinforced ultra-high-performance primer base coat that is highly polymer modified to offer the ultimate adhesion for multiple substrates. With W2 weatherproofing performance it is also highly breathable and utilises our cutting-edge trowel technology which makes the product easy to apply by hand or by spray.

Approvals and Certificates

MOAT 22 & EN-998-1:2016

Technical Data

Pack Size	25kg Bag waterproof packaging
Application Tool	Stainless Steel Trowel, 6mm Notched Trowel
Water Demand	Approx. 4.5 to 6ltr per 25kg bag
Pot Life	1 Hour+
Humidity Requirement	Less than 95%
Coverage	Approx. 1.6kg per mm/per m²
Application Temperature	+3°C to 25°C

Approved Substrates

	NOT Appr
Approved Substrates	Timber
New Concrete Block	Metal
Smooth Brick	Glass
Rough Brick	Below DP
Hacked Off Render	Flat Surfa
Lightweight Block	Insulation
Existing Render (pinned)	Render ca

Not Approved Substrates	
Timber	
Metal	
Glass	
Below DPC	
Flat Surfaces	
Insulation	
Render carrier board	

UK CA Declaration of Performance



Wetherby Laroc Group Dalton Industrial Estate, Dalton, North Yorkshire YO7 3HE

ecorend K11 Key Coat Base

GP: General purpose rendering/plastering mortar BS EN 998-1:2016

Reaction to fire	Class A1
Dry bulk density	1650 kg/m ³
Compressive strength	CS IV
Adhesion	≥ 1.0 N/mm², (FP) B
Capillary water absorption	W2

